




CONCRETE MATTRESS SYSTEMS

- Stabilisation
- Dropped Object Protection
- Scour & Erosion Control
- Cathodic Protection Systems



MODEL : X300 SPECIFICATIONS

| | |
|---|-----------------------|
| BLOCK HEIGHT | 300 mm |
| BLOCK LENGTH | 500 mm |
| BLOCK WIDTH | 500 mm |
| BLOCK VOLUME | 0.0468 m ³ |
| CONCRETE – Volume/Sq.m | 0.187 m ³ |
| WEIGHT –In Air using Concrete Density: 2400 kg/m ³ | 449 kg/m ² |
| WEIGHT – Submerged using seawater Density: 1027 kg/m ³ | 257 kg/m ² |

LIFTING AND STRUCTURAL ROPE

- 4No. ropes per concrete block.
- Lift ropes can be provided on 1, 2 or 4 sides of the mattress.
- Rope diameter selection by FLXMAT™ based on DNV-OS-H205 Lifting Operations.
- Maximum rope diameter is 24mm.

FLXMAT XSERIES offers a range of fully articulating concrete mattresses suitable for Stabilisation, Scour & Erosion Control, Dropped Object and Cathodic Protection.

FLXMAT – Only Limited By Imagination

WWW.FLXMAT.COM